





2X Ø 12MM DOWELS





12X Ø .402 [10.20] THRU ALL
M12X1.75 - 6H ▽ 1.000 [25.40]
EQUALLY SPACED
ON A [230.00] B.C.
Ø 9.055

[230.000±0.013]
9.0551±.0005
[255.0]
Ø 10.04




[235.0]
Ø 9.25


[12.7]
.50
[31.8]
1.25
[150.0]
5.91
[388.0]
15.28
[238.0]
9.37
[69.2]
~ 2.72



STRAIGHT CONNECTOR AVAILABLE ON REQUEST




2X Ø 12MM DOWELS



12X Ø .512 THRU
EQUALLY SPACED
ON A [303.00] B.C.
Ø 11.929

15°



"THIS DRAWING AND ALL DESIGN AND DETAIL SHOWN ON IT ARE THE PROPERTY OF CENTRICITY AND ARE CONFIDENTIAL. THIS DRAWING IS NOT TO BE COPIED WITHOUT WRITTEN PERMISSION OF CENTRICITY. ALL PATENT AND DESIGN RIGHTS ARE RESERVED". COPYRIGHT 2013

TOLERANCES UNLESS OTHERWISE NOTED:
.X = ±.030 .XX = ±.010 .XXX = ±.005 .XXXX = ±.0005
FRACTION ± 1/16 ANGLES ±1 DEG
REMOVE ALL SHARP EDGES AND BURRS

2000F INDEXER WITH BRAKE

SCALE: 1:3	DRAWN BY: C.T.G. DATE: January 29, 2013
DO NOT SCALE	CHECKED BY: DATE:
MODEL FILE: 2000 INDEXER	APPRVD BY: DATE:
REVISION: 0	DRAWING NO.

C2000F-0024

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED